

- PN JP2001261159 A 20010926
- TI MANAGEMENT APPARATUS AND MANAGEMENT METHOD FOR CONTAINER
- FI B65G1/137&A; B65G63/00&J
- PA ISHIKAWAJIMA HARIMA HEAVY IND
- IN KAWASE AKIRA
- AP JP20000084096 20000324
- PR JP20000084096 20000324
- DT -I

© WPI / DERWENT

- **AN** -2002-296052 [34]
- Management device for shipping container, has radio antenna installed at check points, that transmits container number in radio IC tag of container to host computer
- JP2001261159 NOVELTY Radio integrated circuit (IC) number tag (3) with container number is stuck on the outer surface of a container (1). Radio antenna that transmits container number from radio IC tag to host computer (6) is installed at check points in container movement areas.
 - DETAILED DESCRIPTION An INDEPENDENT CLAIM is also included for container management method.
 - USE For supplying containers that are used for transportation of industrial products in sea.
 - ADVANTAGE Since container is arranged based on container number, transmission place, passing through time transmit, etc from the radio IC number tag, movement of container is easy and efficient.
 - DESCRIPTION OF DRAWING(S) The figure shows the diagram of management device of container.
 - Container 1
 - Integrated circuit number tag 3
 - Host computer 6
 - -(Dwg.1/3)
- MANAGEMENT DEVICE SHIPPING CONTAINER RADIO ANTENNA INSTALLATION CHECK POINT TRANSMIT CONTAINER NUMBER RADIO IC TAG CONTAINER HOST COMPUTER
- PN JP2001261159 A 20010926 DW200234 B65G63/00 003pp
- ıc B65G1/137 ;B65G63/00
- mc T01-C03C T01-J05A2B T01-N01A2D W02-C03 W05-D04D W05-D06A1A W05-D08E X25-F
- pc Q35 T01 W02 W05 X25
- PA (ISHI) ISHIKAWAJIMA HARIMA HEAVY IND
- AP JP20000084096 20000324
- PR JP20000084096 20000324

© PAJ / JPO

- PN JP2001261159 A 20010926
- TI MANAGEMENT APPARATUS AND MANAGEMENT METHOD FOR CONTAINER
- AB PROBLEM TO BE SOLVED: To efficiently manage a container.

- -SOLUTION: In this management apparatus, a radio IC number tag 3 inputted with a container number is stuck on the outer face of the container 1, while a checkpoint in a required place in a movement range of the container 1 is installed with a radio antenna 5 receiving/transmitting from/to the radio IC number tag 3. When the container 1 passes the checkpoint, that time, a transmission position and information of the container 1 are transmitted to a host computer 6 from the radio antenna 5, and the host computer 6 manages position information data of the container 1.
- -B65G63/00 ;B65G1/137

PA - ISHIKAWAJIMA HARIMA HEAVY IND CO LTD

IN -KAWASE AKIRA

ABD -20020701

ABV -200026

AP -JP20000084096 20000324

